DETERMINATION OF UNCONFINED COMPRESSIVE STRENGTH

ISRM Suggested Methods, pp 111 –116, 1981.

Hole Number	Sample Number	Sample Type	Top Depth (m)	Base Depth (m)	Sample Diameter (mm)	Sample Length (mm)	Height Ratio	Initial Mass (g)	Bulk Density (Mg/m)	Moisture Content (%)		Load Failure (kN)	UCS (MPa)	Failure Mode	Date Tested	Remarks
WBH112		U	31.50		100	180	1.8	3326	2.35	24	1.90	18.7	2.4	Brittle	05/12/22	

		Contract No:
	Project Otter	PSL22/7303
	Project Otter	Client Ref:
Professional Soils Laboratory		WIE17469

SUMMARY OF POINT LOAD TEST RESULTS

ISRM Suggested Methods: 2007

Borehole Number	Depth (m)	Sample Ref	Test Type	Orientation	Dimei (m		Area	D _e ²	D _e	Failure	Load (P)	\mathbf{I}_{s}	Corr Fac	$\mathbf{I}_{\mathrm{s}50}$	Failure Type	Remarks
ramber		KCI	Турс	Par / Perp	W	D	(mm2)		(mm)	(Mpa)	(kN)	(MPa)	F	(MPa)	Турс	
WBH112	28.50		A	Perp	100	48	4800	6111.55	78.18	-	1.27	0.21	1.223	0.25	Valid	

*Note All testing carried out on samples at as received water content

Par = parallel, Perp = perpendicular, U = Random

A = Axial, D = Diametral, I = Irregular





Contract No:	
PSL22/7303	
Client Ref:	
WIE17469	

SUMMARY OF POINT LOAD TEST RESULTS

ISRM Suggested Methods: 2007

Borehole Number	Depth (m)	Sample Ref	Test Type	Orientation	Dimer (m	nsions m)	D _e ²	$\mathbf{D}_{\mathbf{e}}$	Failur	e Load	\mathbf{I}_{s}	Corr Fac	I_{s50}	Failure Type	Remarks
Number	(111)	KCI	Турс	Par / Perp	L	D		(mm)	(Mpa)	(kN)	(MPa)	F	(MPa)	Турс	
WBH112	28.50		D	Par	-	100	10000	100.00	-	1.05	0.105	1.366	0.14	Valid	
			<u> </u>						11.1.5		1 11 5				

 $\underline{*Note}$ All testing carried out on samples at as received water content

Par = parallel, Perp = perpendicular, U = Random





Project Otter



LABORATORY REPORT



4043

Contract Number: PSL22/7304

Report Date: 14 December 2022

Client's Reference: WIE17469-WBH113

Client Name: Groundtech Consulting

First Floor Lloyd House Orford Court Greenfold Way WN7 3XJ

For the attention of: Jamie Parr

Contract Title: Project Otter

Date Received: 14/11/2022
Date Commenced: 14/11/2022
Date Completed: 14/12/2022

Notes: Opinions and Interpretations are outside the UKAS Accreditation

A copy of the Laboratory Schedule of accredited tests as issued by UKAS is attached to this report. This certificate is issued in accordance with the accreditation requirements of the United Kingdom Accreditation Service. The results reported herein relate only to the material supplied to the laboratory. This certificate shall not be reproduced other than in full, without the prior written approval of the laboratory.

Checked and Approved Signatories:

A Watkins R Berriman S Royle (Director) (Quality Manager) (Laboratory Manager)

L Knight S Eyre T Watkins
(Assistant Laboratory Manager) (Senior Technician) (Senior Technician)

5 – 7 Hexthorpe Road, Hexthorpe,

Doncaster DN4 0AR tel: +44 (0)844 815 6641 fax: +44 (0)844 815 6642

e-mail: rberriman@prosoils.co.uk awatkins@prosoils.co.uk

Page 1 of

SUMMARY OF LABORATORY SOIL DESCRIPTIONS

Hole Number	Sample Number	Sample Type	Top Depth m	Base Depth m	Description of Sample
WBH113		В	1.00		Brown very gravelly clayey SAND.
WBH113		D	1.70		Brown gravelly SAND.
WBH113		В	2.00		Light brown gravelly clayey SAND
WBH113		U	7.50		Stiff grey CLAY.
WBH113		В	8.00		Grey CLAY.
WBH113		U	16.50		Stiff grey CLAY.
WBH113		В	17.00		Grey CLAY.
WBH113		В	26.00		Grey CLAY.
WBH113		U	34.50		Very stiff grey CLAY.



Contract No:						
PSL22/7304						
Client Ref:						
WIE71469						


SUMMARY OF SOIL CLASSIFICATION TESTS

(BS1377: PART 2: 1990)


Hole Number	Sample Number	Sample Type	Top Depth	Base Depth	Moisture Content %	Linear Shrinkage %	Particle Density Mg/m ³	Liquid Limit %	Plastic Limit %	Plasticity Index %	Passing .425mm	Remarks
			m	m	Clause 3.2	Clause 6.5	Clause 8.2	Clause 4.3/4	Clause 5.3	Clause 5.4		
WBH113		D	1.70		14							
WBH113		В	8.00		33			83	31	52	100	Very High Plasticity CV
WBH113		В	17.00		30			89	32	57	100	Very High Plasticity CV
WBH113		В	26.00		30			83	31	52	100	Very High Plasticity CV

SYMBOLS: NP: Non Plastic

^{*:} Liquid Limit and Plastic Limit Wet Sieved.



PLASTICITY CHART FOR CASAGRANDE CLASSIFICATION.






Project Otter

BS1377 : Part 2 : 1990 Wet Sieve, Clause 9.2

Hole Number: WBH113 Top Depth (m): 1.00

Sample Number: Base Depth(m):

Sample Type: B



BS Test	Percentage
Sieve (mm)	Passing
125	100
75	100
63	100
37.5	100
20	92
10	90
6.3	85
3.35	75
2	63
1.18	50
0.6	36
0.3	22
0.212	16
0.15	13
0.063	11

Soil	Total
Fraction	Percentage
Cobbles Gravel Sand Silt/Clay	0 37 52 11

Remarks:

See Summary of Soil Descriptions





Contract No:
PSL22/7304
Client Ref:
WIE71469


BS1377: Part 2: 1990

Wet Sieve & Pipette Analysis, Clause 9.2 & 9.4

Hole Number: WBH113 Top Depth (m): 8.00

Sample Number: Base Depth(m):

Sample Type: B



BS Test	Percentage
Sieve (mm)	Passing
125	100
75	100
63	100
37.5	100
20	100
10	100
6.3	100
3.35	100
2	100
1.18	100
0.6	100
0.3	100
0.212	100
0.15	100
0.063	99

Particle	Percentage					
Diameter	Passing					
0.02	93					
0.006	78					
0.002	57					

Soil	Total					
Fraction	Percentage					
Cobbles	0					
Gravel	0					
Sand	1					
Silt	42					
Clay	57					

Remarks:

See Summary of Soil Descriptions





Contract No:
PSL22/7304
Client Ref:
WIE71469


BS1377: Part 2: 1990

Wet Sieve & Pipette Analysis, Clause 9.2 & 9.4

Hole Number: WBH113 Top Depth (m): 17.00

Sample Number: Base Depth(m):

Sample Type: B



BS Test	Percentage					
Sieve (mm)	Passing					
125	100					
75	100					
63	100					
37.5	100					
20	100					
10	100 100 100 100 100 100					
6.3						
3.35						
2						
1.18						
0.6						
0.3	100					
0.212	100					
0.15	100					
0.063	100					

Particle	Percentage					
Diameter	Passing					
0.02	94					
0.006	80					
0.002	59					

Soil	Total					
Fraction	Percentage					
Cobbles	0					
Gravel	0					
Sand	0					
Silt	41					
Clay	59					

Remarks:

See Summary of Soil Descriptions





Contract No:
PSL22/7304
Client Ref:
WIE71469


BS1377: Part 2: 1990

Wet Sieve & Pipette Analysis, Clause 9.2 & 9.4

Hole Number: WBH113 Top Depth (m): 26.00

Sample Number: Base Depth(m):

Sample Type: B



BS Test	Percentage					
Sieve (mm)	Passing					
125	100					
75	100					
63	100					
37.5	100					
20	100					
10	100 100 100 100 100 100					
6.3						
3.35						
2						
1.18						
0.6						
0.3	100					
0.212	100					
0.15	99					
0.063	99					

Particle	Percentage					
Diameter	Passing					
0.02	95					
0.006	81					
0.002	56					

Soil	Total					
Fraction	Percentage					
Cobbles	0					
Gravel	0					
Sand	1					
Silt	43					
Clay	56					

Remarks:

See Summary of Soil Descriptions





Contract No:
PSL22/7304
Client Ref:
WIE71469


WITHOUT MEASUREMENT OF PORE PRESSURE

BS1377: Part7: 1990: Clause 8

Hole Number: WBH113 Top Depth (m): 7.50

Sample Number: Base Depth (m):

Sample Type: U



Diamet	er (mm):	38.0 Height (mm):		76.0 Test:		3x38mm Samples.		ples.	Remarks	
		Moisture	Bulk	Dry	Cell	Deviator	Shear	Failure	Mode	Undisturbed Sample
Specime n	Specimen Depth	Content	Density	Density	Pressure	Stress	Strength	Strain	of	Specimens obtained by use of 3x38mm cutters
		(%)	(Mg/m3)	(Mg/m3)	(kPa)	(kPa)	(kPa)	(%)	Failure	Rate of strain - 2%/min Latex membrane used 0.2mm
1	7.50	25	1.86	1.49	75	179	90	10.5	Brittle	See summary of soil descriptions
2	7.50	25	1.86	1.48	150	220	110	14.2	Brittle	
3	7.50	25	1.86	1.48	300	246	123	13.7	Brittle	



	Contract No:
Dualant Otton	PSL22/7304
Project Otter	Client Ref:
	WIE71469


WITHOUT MEASUREMENT OF PORE PRESSURE

BS1377: Part7: 1990: Clause 8

Hole Number: WBH113 Top Depth (m): 16.50

Sample Number: Base Depth (m):

Sample Type U



Diamete	er (mm):	103	Height	(mm):	207	Test:	UU Sing	gle Stage	Remarks:
Specimen	Moisture	Bulk	Dry	Cell	Corr. Max.	Shear	Failure	Mode	Undisturbed Sample
	Content	Density	Density	Pressure	Deviator	Strength	Strain	of	Sample taken from top of tube
	(%)	(Mg/m3)	(Mg/m3)	(kPa)	Stress	Cu	(%)	Failure	Rate of strain = 2 %/min
					(kPa)	(kPa)			Latex Membrane used 0.2 mm thick,
				3	(_{1 3}) _f	$^{1}/_{2}(_{1} _{3})_{f}$			Correction applied 0.36
1	28	1.94	1.52	330	232	116	4.0	Brittle	See summary of soil descriptions



Project Otter

Contract No:
PSL22/7304
Client Ref:
WIE71469


WITHOUT MEASUREMENT OF PORE PRESSURE

BS1377: Part7: 1990: Clause 8

Hole Number: WBH113 Top Depth (m): 34.50

Sample Number: Base Depth (m):

Sample Type U



Diamete	Diameter (mm):		Height (mm):		Height (mm):		207	Test:	UU Sing	gle Stage	Remarks:
Specimen	Moisture	Bulk	Dry	Cell	Corr. Max.	Shear	Failure	Mode	Undisturbed Sample		
	Content	Density	Density	Pressure	Deviator	Strength	Strain	of	Sample taken from top of tube		
	(%)	(Mg/m3)	(Mg/m3)	(kPa)	Stress	Cu	(%)	Failure	Rate of strain = 2 %/min		
					(kPa)	(kPa)			Latex Membrane used 0.2 mm thick,		
				3	(_{1 3}) _f	$^{1}/_{2}(_{1} _{3})_{f}$			Correction applied 0.36		
1	26	1.86	1.47	690	494	247	6.5	Brittle	See summary of soil descriptions		




	Contract No:
Project Otton	PSL22/7304
Project Otter	Client Ref:
	WIE71469

CONSOLIDATED DRAINED SHEARBOX TEST

BS1377:Part 7:1990 Clause 4

Hole Number:		WBH113	Top Depth	ı:	2.00	
Sample Number:			Base Dept	h:		
Sample Conditions:		Dry	Sample Ty	/ре	3	
Particle Density - Mg/m3:	2.65	Assumed	Remarks			
Sample Preparation:	Material test	ed passing 2mm sieve				
Sample I Teparation.	Remoulded 1	using hand tamped effor				
Sample Description:	See summar	y of soil descriptions.				
STAGE				1	2	3
		Initial Conditions				
Height - mm:				19.99	19.99	19.99
Length - mm:				60.05	60.05	60.05
Moisture Content - %:				17	17	17
Bulk Density - Mg/m3:				2.10	2.10	2.10
Dry Density - Mg/m3:	1.79	1.79	1.79			
Voids Ratio:				0.479	0.479	0.480
Normal Pressure- kPa				20	40	80
		Consolidation Stag	ge			
Consolidated Height - mm:				19.88	19.69	19.43
		Shearing Stage				
Rate of Strain - mm/min				0.60	0.60	0.60
Displacement at peak shear s	tress - mm			2.71	3.01	3.62
Peak shear Stress - kPa:				27	42	72
	Fi	nal Consolidated Con-	ditions			
Moisture Content - %:				16	16	15
Bulk Density - Mg/m3:				2.11	2.13	2.16
Dry Density - Mg/m3:				1.83	1.84	1.88
Peak						
Angle of Shearing Resistance	36					
Effective Cohesion - kPa:					13	









Contract No:
PSL22/7304
Client Ref:
WIE71469


CONSOLIDATED DRAINED SHEARBOX TEST

BS1377:Part 7:1990 Clause 4

Hole Number:	WBH113	Top Depth:	2.00
Sample Number:		Base Depth:	











Contract No:
PSL22/7304
Client Ref:
WIE71469



LABORATORY REPORT



4043

Contract Number: PSL22/7302

Report Date: 20 December 2022

Client's Reference: WIE17469-WBH114

Client Name: Groundtech Consulting

First Floor Lloyd House Orford Court Greenfold Way WN7 3XJ

For the attention of: Jamie Parr

Contract Title: Project Otter

Date Received: 14/11/2022 Date Commenced: 14/11/2022 Date Completed: 15/12/2022

Notes: Opinions and Interpretations are outside the UKAS Accreditation

A copy of the Laboratory Schedule of accredited tests as issued by UKAS is attached to this report. This certificate is issued in accordance with the accreditation requirements of the United Kingdom Accreditation Service. The results reported herein relate only to the material supplied to the laboratory. This certificate shall not be reproduced other than in full, without the prior written approval of the laboratory.

Checked and Approved Signatories:

A Watkins R Berriman (Director) (Quality Manager)

S Royle

(Laboratory Manager)

L Knight S Eyre (Senior Technician) (Senior Technician)

T Watkins (Senior Technician)

Page 1 of

5 – 7 Hexthorpe Road, Hexthorpe,

Doncaster DN4 0AR

tel: +44 (0)844 815 6641 fax: +44 (0)844 815 6642

e-mail: awatkins@prosoils.co.uk rberriman@prosoils.co.uk

SUMMARY OF LABORATORY SOIL DESCRIPTIONS

Hole Number	Sample Number	Sample Type	Top Depth m	Base Depth m	Description of Sample
WBH114		В	0.80		Brown sandy GRAVEL.
WBH114		В	1.50		Brown mottled grey slightly gravelly very sandy CLAY.
WBH114		В	4.00		Brown mottled grey slightly gravelly very sandy CLAY.
WBH114		U	6.00		Brown mottled grey CLAY.
WBH114		В	7.00		Brown mottled grey CLAY.
WBH114		U	12.00		Stiff brown mottled grey CLAY.
WBH114		В	17.00		Brown mottled grey CLAY.
WBH114		U	18.00		Very stiff brown mottled grey CLAY.
WBH114		U	24.00		Stiff grey slightly sandy CLAY.
WBH114		U	30.00		Grey slightly sandy CLAY.
WBH114		U	36.00		Stiff grey CLAY.



Project Otter


SUMMARY OF SOIL CLASSIFICATION TESTS

(BS1377: PART 2: 1990)


Hole Number	Sample Number	Sample Type	Top Depth	Base Depth	Moisture Content %	Linear Shrinkage %	Particle Density Mg/m³	Liquid Limit %	Plastic Limit %	Plasticity Index %	Passing .425mm	Remarks
			m	m	Clause 3.2	Clause 6.5	Clause 8.2	Clause 4.3/4	Clause 5.3	Clause 5.4		
WBH114		В	1.50		20							
WBH114		В	7.00		30			72	29	43	100	Very High Plasticity CV
WBH114		В	17.00		31			74	30	44	100	Very High Plasticity CV
WBH114		U	30.00		28			60	26	34	100	High Plasticity CH

SYMBOLS: NP: Non Plastic

^{*:} Liquid Limit and Plastic Limit Wet Sieved.



PLASTICITY CHART FOR CASAGRANDE CLASSIFICATION.






Project Otter

BS1377 : Part 2 : 1990 Wet Sieve, Clause 9.2

Hole Number: WBH114 Top Depth (m): 1.50

Sample Number: Base Depth(m):

Sample Type: B



BS Test	Percentage
Sieve (mm)	Passing
125	100
75	100
63	100
37.5	100
20	100
10	100
6.3	99
3.35	97
2	96
1.18	95
0.6	93
0.3	86
0.212	80
0.15	75
0.063	67

Soil	Total
Fraction	Percentage
Cobbles Gravel Sand Silt/Clay	0 4 29 67

Remarks:

See Summary of Soil Descriptions





Contract No:
PSL22/7302
Client Ref:
WIE17469


BS1377: Part 2: 1990

Wet Sieve & Pipette Analysis, Clause 9.2 & 9.4

Hole Number: WBH114 Top Depth (m): 4.00

Sample Number: Base Depth(m):

Sample Type: B



BS Test	Percentage
Sieve (mm)	Passing
125	100
75	100
63	100
37.5	100
20	100
10	100
6.3	99
3.35	98
2	98
1.18	97
0.6	96
0.3	93
0.212	90
0.15	85
0.063	77

Particle	Percentage
Diameter	Passing
0.02	65
0.006	49
0.002	34

Soil	Total
Fraction	Percentage
Cobbles	0
Gravel	2
Sand	21
Silt	43
Clay	34

Remarks:

See Summary of Soil Descriptions





Contract No:
PSL22/7302
Client Ref:
WIE17469


BS1377: Part 2: 1990

Wet Sieve & Pipette Analysis, Clause 9.2 & 9.4

Hole Number: WBH114 Top Depth (m): 7.00

Sample Number: Base Depth(m):

Sample Type: B



BS Test	Percentage
Sieve (mm)	Passing
125	100
75	100
63	100
37.5	100
20	100
10	100
6.3	100
3.35	100
2	100
1.18	100
0.6	100
0.3	100
0.212	100
0.15	99
0.063	99

Particle	Percentage
Diameter	Passing
0.02	92
0.006	72
0.002	46

Soil	Total
Fraction	Percentage
Cobbles	0
Gravel	0
Sand	1
Silt	53
Clay	46

Remarks:

See Summary of Soil Descriptions





Contract No:
PSL22/7302
Client Ref:
WIE17469


BS1377: Part 2: 1990

Wet Sieve & Pipette Analysis, Clause 9.2 & 9.4

Hole Number: WBH114 Top Depth (m): 17.00

Sample Number: Base Depth(m):

Sample Type: B



BS Test	Percentage
Sieve (mm)	Passing
125	100
75	100
63	100
37.5	100
20	100
10	100
6.3	100
3.35	100
2	100
1.18	100
0.6	100
0.3	100
0.212	100
0.15	100
0.063	100

Particle	Percentage
Diameter	Passing
0.02	93
0.006	72
0.002	43

Soil	Total
Fraction	Percentage
Cobbles	0
Gravel	0
Sand	0
Silt	57
Clay	43

Remarks:

See Summary of Soil Descriptions





Contract No:
PSL22/7302
Client Ref:
WIE17469


BS1377: Part 2: 1990

Wet Sieve & Pipette Analysis, Clause 9.2 & 9.4

Hole Number: WBH114 Top Depth (m): 30.00

Sample Number: Base Depth(m):

Sample Type: U



BS Test	Percentage
Sieve (mm)	Passing
125	100
75	100
63	100
37.5	100
20	100
10	100
6.3	100
3.35	99
2	99
1.18	99
0.6	98
0.3	98
0.212	97
0.15	95
0.063	90

Particle	Percentage
Diameter	Passing
0.02	79
0.006	61
0.002	42

Soil	Total
Fraction	Percentage
Cobbles	0
Gravel	1
Sand	9
Silt	48
Clay	42

Remarks:

See Summary of Soil Descriptions





Contract No:
PSL22/7302
Client Ref:
WIE17469


WITHOUT MEASUREMENT OF PORE PRESSURE

BS1377: Part7: 1990: Clause 8

Hole Number: WBH114 Top Depth (m): 12.00

Sample Number: Base Depth (m):

Sample Type U



Diamete	er (mm):	103	Height	(mm):	207	Test:	UU Single Stage		Remarks:	
Specimen	Moisture	Bulk	Dry	Cell	Corr. Max.	Max. Shear Failure Mode Undisturbed Sampl		Undisturbed Sample		
	Content	Density	Density	Pressure	Deviator	Strength	Strain	of	Sample taken from top of tube	
	(%)	(Mg/m3)	(Mg/m3)	(kPa)	Stress	Cu	(%)	Failure	Rate of strain = 2 %/min	
					(kPa)	(kPa)			Latex Membrane used 0.2 mm thick,	
				3	(_{1 3}) _f	$^{1}/_{2}(_{1} _{3})_{f}$			Correction applied 0.36	
1	28	1.92	1.50	240	154	77	3.5	Brittle	See summary of soil descriptions	



	Contract No:
Project Otton	PSL22/7302
Project Otter	Client Ref:
	WIE17469


WITHOUT MEASUREMENT OF PORE PRESSURE

BS1377: Part7: 1990: Clause 8

Hole Number: WBH114 Top Depth (m): 18.00

Sample Number: Base Depth (m):

Sample Type U



Diamete	er (mm):	103	Height	(mm):	207	Test:	UU Single Stage		Remarks:	
Specimen	Moisture	Bulk	Dry	Cell	Corr. Max.	Shear	Failure	Mode	Undisturbed Sample	
	Content	Density	Density	Pressure	Deviator	Strength	Strain	of	Sample taken from top of tube	
	(%)	(Mg/m3)	(Mg/m3)	(kPa)	Stress	Cu	(%)	Failure	Rate of strain = 2 %/min	
					(kPa)	(kPa)			Latex Membrane used 0.2 mm thick,	
				3	(_{1 3}) _f	$^{1}/_{2}(_{1} _{3})_{f}$			Correction applied 0.36	
1	27	1.94	1.52	360	366	183	3.5	Brittle	See summary of soil descriptions	



Project Otter


WITHOUT MEASUREMENT OF PORE PRESSURE

BS1377: Part7: 1990: Clause 8

Hole Number: WBH114 Top Depth (m): 24.00

Sample Number: Base Depth (m):

Sample Type U



Diamete	er (mm):	103	Height	(mm):	207	Test:	UU Single Stage		Remarks:	
Specimen	Moisture	Bulk	Dry	Cell	Corr. Max.	Shear	Failure	Mode	Undisturbed Sample	
	Content	Density	Density	Pressure	Deviator	Strength	Strain	of	Sample taken from top of tube	
	(%)	(Mg/m3)	(Mg/m3)	(kPa)	Stress	Cu	(%)	Failure	Rate of strain = 2 %/min	
					(kPa)	(kPa)			Latex Membrane used 0.2 mm thick,	
				3	(_{1 3}) _f	$^{1}/_{2}(_{1} _{3})_{f}$			Correction applied 0.35	
1	26	1.90	1.51	120	277	139	10.0	Brittle	See summary of soil descriptions	

^{*} Single stage test due to early brittle failure



Project Otter


WITHOUT MEASUREMENT OF PORE PRESSURE

BS1377: Part7: 1990: Clause 8

Hole Number: WBH114 Top Depth (m): 36.00

Sample Number: Base Depth (m):

Sample Type: U



Diameter (mm): 38.0		Height (mm):		76.0	Test:	3x38mm Samples.		ples.	Remarks	
		Moisture	Bulk	Dry	Cell	Deviator	Shear	Failure	Mode	Undisturbed Sample
Specime n	Specimen Depth	Content	Density	Density	Pressure	Stress	Strength	Strain	of	Specimens obtained by use of 3x38mm cutters
		(%)	(Mg/m3)	(Mg/m3)	(kPa)	(kPa)	(kPa)	(%)	Failure	Rate of strain - 2%/min Latex membrane used 0.2mm
1	36.00	29	1.76	1.37	360	223	112	9.5	Brittle	See summary of soil descriptions
2	36.00	29	1.76	1.37	720	256	128	7.4	Brittle	
3	36.00	29	1.76	1.37	1440	316	158	12.1	Brittle	

Set of 38mm due to intact material





Project Otter


CALIFORNIA BEARING RATIO TEST

BS 1377: Part 4: 1990

Hole Number: WBH114 Top Depth (m): 0.80

Sample Number: Base Depth (m):

Sample Type: B



Initial Sample Conditions		Sample Prepara	ation	Final Moisture Con	C.B.R. Value %		
Moisture Content:	11	Surcharge Kg:	4.20	Sample Top	11	Sample Top	139.9
Bulk Density Mg/m3:	2.24	Soaking Time hrs	0	Sample Bottom	11	Sample Bottom	160.1
Dry Density Mg/m3:	2.01	Swelling mm:	0.00	Remarks : See Summary of Soil Descriptions.			
Percentage retained on 2	20mm B	S test sieve:	12	2			
Compaction Conditions 2.5kg							



ONE DIMENSIONAL CONSOLIDATION TEST


BS 1377: Part 5: 1990: Clause 3

Hole Number: WBH114 Top Depth (m): 6.00


Sample Number: Base Depth (m): 6.00

Sample Type: U

Initial Conditions		Pressure	Range	Mv	Cv	Specimen location			
Moisture Content (%):	32	kPa		m2/MN	m2/yr	within tube: Top			
Bulk Density (Mg/m3):	1.91	0 60		0.213	4.264	Method used to			
Dry Density (Mg/m3):	1.44	60	120	0.201	1.682	determine CV: T90			
Voids Ratio:	0.839	120	240	0.189	1.086	Nominal temperature			
Degree of saturation:	102.4	240	120	0.062	1.285	during test 'C: 20			
Height (mm):	20.02	120	60	0.149	1.065	Remarks:			
Diameter (mm)	75.01	60	3	0.674	0.214	See summary of soil descriptions			
Particle Density (Mg/m3):	2.65	3	60	0.334	1.325				
Assumed	2.03	60	120	0.250	1.322				



Pressure -kPa







Project C	Otter
-----------	-------

Contract No:
PSL22/7302
Client Ref:
WIE17469



TEST AMENDMENT NOTICE

(Please tick boxes as appropriate)	^			
	To: Jamie Part			
Date: 7 / \2_/2022	Laboratory Ref: PS2217302			
Contract Number:	Location: Project Otter			
	Depth (m):			
Sample Type: o B o I Test/s:	D o W o P o C			
WBH114 3.50 60				
The above sample cannot be tested for the follow	ving reasons:			
The Sample has not been received There is insufficient material for BS1377 Maximum Grain Size Sample Mass (kg): Required Mass (kg):				
 The Sample has been previously tested. The Sample has been misplaced in the La The Sample is unsuitable for testing became 				
Please advise action required: Perform original test on the following alt BH O TP Sample Type: O U	Sample Number: Depth (m):			
Combine original Sample with the follow O BH O TP	ving sample: Sample Number: Depth (m):			
Sample Type: o	U oB oD oW oP oC			
□ Perform the following alternative test/s o	n the original Sample			
□ Perform non-standard test on material available				
□ Take no further action.				
Signed(Project Engineer)	Date			





Issued:

Certificate Number 22-25483

Client Professional Soils Laboratory Ltd

5/7 Hexthorpe Road

Hexthorpe DN4 0AR

Our Reference 22-25483

Client Reference PSL22/7302

Order No (not supplied)

Contract Title WIE17469: Project Otter

Description One Soil sample.

Date Received 09-Dec-22

Date Started 09-Dec-22

Date Completed 15-Dec-22

Test Procedures Identified by prefix DETSn (details on request).

Notes Opinions and interpretations are outside the laboratory's scope of ISO 17025 accreditation. This certificate is issued in accordance with the accreditation requirements of the United Kingdom Accreditation Service. The results reported herein relate only to the material supplied to the laboratory. This certificate shall not be reproduced except in full, without the prior written approval of the laboratory.

Approved By

Kirk Bridgewood General Manager





15-Dec-22



Summary of Chemical Analysis Soil Samples

Our Ref 22-25483 Client Ref PSL22/7302 Contract Title WIE17469: Project Otter

Lab No	2096368
.Sample ID	WBH114
Depth	3.00
Other ID	
Sample Type	SOIL
Sampling Date	
Sampling Time	n/s

Test	Method	LOD	Units		
Metals					
Magnesium Aqueous Extract	DETSC 2076*	10	mg/l	< 10	
Inorganics					
рН	DETSC 2008#		рН	8.0	
Chloride Aqueous Extract	DETSC 2055	1	mg/l	13	
Nitrate Aqueous Extract as NO3	DETSC 2055	1	mg/l	20	
Sulphate Aqueous Extract as SO4	DETSC 2076#	10	mg/l	93	
Sulphur as S, Total	DETSC 2320	0.01	%	0.03	
Sulphate as SO4, Total	DETSC 2321#	0.01	%	0.08	



Information in Support of the Analytical Results

Our Ref 22-25483 Client Ref PSL22/7302

Contract WIE17469: Project Otter

Containers Received & Deviating Samples

		Date			container for
Lab No	Sample ID	Sampled	Containers Received	Holding time exceeded for tests	tests
2096368	WBH114 3.00 SOIL	12/11/22	PT 500ml	Total Sulphur ICP (7 days), pH + Conductivity (7 days)	

Key: P-Plastic T-Tub

DETS cannot be held responsible for the integrity of samples received whereby the laboratory did not undertake the sampling. In this instance samples received may be deviating. Deviating Sample criteria are based on British and International standards and laboratory trials in conjunction with the UKAS note 'Guidance on Deviating Samples'. All samples received are listed above. However, those samples that have additional comments in relation to hold time, inappropriate containers etc are deviating due to the reasons stated. This means that the analysis is accredited where applicable, but results may be compromised due to sample deviations. If no sampled date (soils) or date+time (waters) has been supplied then samples are deviating. However, if you are able to supply a sampled date (and time for waters) this will prevent samples being reported as deviating where specific hold times are not exceeded and where the container supplied is suitable.

Soil Analysis Notes

Inorganic soil analysis was carried out on a dried sample, crushed to pass a 425µm sieve, in accordance with BS1377.

Organic soil analysis was carried out on an 'as received' sample. Organics results are corrected for moisture and expressed on a dry weight basis.

The Loss on Drying, used to express organics analysis on an air dried basis, is carried out at a temperature of 28°C +/-2°C.

Disposal

From the issue date of this test certificate, samples will be held for the following times prior to disposal :-Soils - 1 month, Liquids - 2 weeks, Asbestos (test portion) - 6 months

End of Report



LABORATORY REPORT



Contract Number: PSL23/0045

Report Date: 17 January 2023

Client's Reference: WIE17469

Client Name: Groundtech Consulting

First Floor Lloyd House Orford Court Greenfold Way WN7 3XJ

For the attention of: Michael Berry

Contract Title: Project Otter

Date Received: 23/12/2022
Date Commenced: 23/12/2022
Date Completed: 17/1/2023

Notes: Opinions and Interpretations are outside the UKAS Accreditation

A copy of the Laboratory Schedule of accredited tests as issued by UKAS is attached to this report. This certificate is issued in accordance with the accreditation requirements of the United Kingdom Accreditation Service. The results reported herein relate only to the material supplied to the laboratory. This certificate shall not be reproduced other than in full, without the prior written approval of the laboratory.

Checked and Approved Signatories:

A Watkins R Berriman S Royle (Director) (Quality Manager) (Laboratory Manager)

L Knight S Eyre T Watkins
(Assistant Laboratory Manager) (Senior Technician) (Senior Technician)

5-7 Hexthorpe Road,

Hexthorpe, Doncaster, DN4 0AR

Tel: 01302 768098

Email: rberriman@prosoils.co.uk awatkins@prosoils.co.uk

Page 1 of

SUMMARY OF LABORATORY SOIL DESCRIPTIONS

Hole Number	Sample Number	Sample Type	Top Depth m	Base Depth m	Description of Sample
WBH115		U	1.50		Stiff brown mottled grey slightly gravelly slightly sandy CLAY. Gravel is chalk.
WBH115		D	2.00		Brown mottled grey slightly gravelly slightly sandy CLAY.
WBH115		U	9.00		Very stiff brown mottled grey slightly sandy CLAY.
WBH115		В	9.50		Brown mottled grey slightly gravelly CLAY.
WBH115		U	15.00		SB
WBH115		В	29.50		Brown mottled grey CLAY.
WBH115		U	30.00		Hard brown CLAY.
WBH115		U	36.00		SB





Project Otter

Contract No:
PSL23/0045
Client Ref:
WIE17469

PSLRF011 Issue No.1 Approved by: L Pavey 03/01/2022

SUMMARY OF SOIL CLASSIFICATION TESTS

(BS1377: PART 2: 1990)

					Moisture	Linear	Particle	Liquid	Plastic	Plasticity	Passing	
Hole	Sample	Sample	Top	Base	Content	Shrinkage		Limit	Limit	Index	.425mm	Remarks
Number	Number	Type	Depth	Depth	%	%	Mg/m^3	%	%	%	%	
			m	m	Clause 3.2	Clause 6.5	Clause 8.2	Clause 4.3/4	Clause 5.3	Clause 5.4		
WBH115		D	2.00		24			60	26	34	97	High Plasticity CH
WBH115		В	9.50		26			72	30	42	99	Very High Plasticity CV
WBH115		В	29.50		29			76	32	44	100	Very High Plasticity CV

SYMBOLS: NP: Non Plastic

*: Liquid Limit and Plastic Limit Wet Sieved.






Project Otter

Contract No:
PSL23/0045
Client Ref:
WIE 7469

PSLRF006 Issue No.1 Approved By: L Pavey 03/01/2023

PLASTICITY CHART FOR CASAGRANDE CLASSIFICATION.







Project Otter

Contract No:
PSL23/0045
Client Ref:
WIE 7469

PSLRF006

Issue No.1

Approved By: L Pavey


03/01/2023

BS1377 : Part 2 : 1990 Wet Sieve, Clause 9.2

Hole Number: WBH115 Top Depth (m): 2.00

Sample Number: Base Depth(m):

Sample Type: D



BS Test	Percentage
Sieve (mm)	Passing
125	100
75	100
63	100
37.5	100
20	100
10	100
6.3	100
3.35	100
2	99
1.18	99
0.6	98
0.3	97
0.212	95
0.15	94
0.063	90

Soil	Total
Fraction	Percentage
Cobbles Gravel Sand Silt/Clay	0 1 9 90

Remarks:

See Summary of Soil Descriptions





Project Otter

Contract No:
PSL23/0045
Client Ref:
WIE17469


PSLRF015 Issue No.1 Approved by: L Pavey 03/01/2023

BS1377 : Part 2 : 1990 Wet Sieve, Clause 9.2

Hole Number: WBH115 Top Depth (m): 9.50

Sample Number: Base Depth(m):

Sample Type: B



BS Test	Percentage					
Sieve (mm)	Passing					
125	100					
75	100					
63	100					
37.5	100					
20	100					
10	100					
6.3	100					
3.35	100					
2	99					
1.18	99					
0.6	99					
0.3	99					
0.212	99					
0.15	99					
0.063	98					

Soil	Total
Fraction	Percentage
Cobbles Gravel Sand Silt/Clay	0 1 1 98

Remarks:

See Summary of Soil Descriptions





Project Otter

Contract No: PSL23/0045 Client Ref: WIE17469

PSLRF015 Issue No.1 Approved by: L Pavey 03/01/2023


WITHOUT MEASUREMENT OF PORE PRESSURE

BS1377: Part7: 1990: Clause 8

Hole Number: WBH115 Top Depth (m): 1.50

Sample Number: Base Depth (m):

Sample Type U



Diamete	er (mm):	103	Height	(mm):	207	Test:	UU Single Stage		Remarks:	
Specimen	Moisture	Bulk	Dry	Cell	Corr. Max.	Shear	Failure Mode		Undisturbed Sample	
	Content	Density	Density	Pressure	Deviator	Strength	Strain	of	Sample taken from top of tube	
	(%)	(Mg/m3)	(Mg/m3)	(kPa)	Stress	Cu	(%) Failure		Rate of strain = 2 %/min	
					(kPa)	(kPa)			Latex Membrane used 0.2 mm thick,	
				3	$(_{1} _{3})_{f}$	$^{1}/_{2}(_{1} _{3})_{f}$			Correction applied 0.36	
1	24	1.91	1.54	30	159	79	7.0	Brittle	See summary of soil descriptions	



Project Otter

Contract No:
PSL23/0045
Client Ref:
WIE17469

PSLRF025 Issue No.1 Approved by: L Pavey 03/01/202


WITHOUT MEASUREMENT OF PORE PRESSURE

BS1377: Part7: 1990: Clause 8

Hole Number: WBH115 Top Depth (m): 9.00

Sample Number: Base Depth (m):

Sample Type U



Dian	neter (mm):	103	Height	(mm):	207	Test:	UU Single Stage		Remarks:	
Specin	en Moisture	Bulk	Dry	Cell	Corr. Max.	Shear	Failure	Mode	Undisturbed Sample	
	Content	Density	Density	Pressure	Deviator	Strength	Strain	of	Sample taken from top of tube	
	(%)	(Mg/m3)	(Mg/m3)	(kPa)	Stress	Cu	(%)	Failure	Rate of strain = 2 %/min	
					(kPa)	(kPa)			Latex Membrane used 0.2 mm thick,	
				3	$(_{1} _{3})_{f}$	$^{1}/_{2}(_{1} _{3})_{f}$			Correction applied 0.36	
1	26	1.91	1.52	180	362	181	7.5	Brittle	See summary of soil descriptions	





Project Otter

Contract No:
PSL23/0045
Client Ref:
WIE17469

PSLRF025 Issue No.1 Approved by: L Pavey 03/01/202


WITHOUT MEASUREMENT OF PORE PRESSURE

BS1377: Part7: 1990: Clause 8

Hole Number: WBH115 Top Depth (m): 30.00

Sample Number: Base Depth (m):

Sample Type U



Diamete	er (mm):	103	Height	(mm):	207	Test:	UU Single Stage		Remarks:	
Specimen	Moisture	Bulk	Dry	Cell	Corr. Max.	Shear	Failure Mode		Undisturbed Sample	
	Content	Density	Density	Pressure	Deviator	Strength	Strain of		Sample taken from top of tube	
	(%)	(Mg/m3)	(Mg/m3)	(kPa)	Stress	Cu	(%) Failure		Rate of strain = 2 %/min	
					(kPa)	(kPa)			Latex Membrane used 0.2 mm thick,	
				3	$(_{1} _{3})_{f}$	$^{1}/_{2}(_{1} _{3})_{f}$			Correction applied 0.36	
1	24	1.95	1.57	600	632	316	5.0 Brittle		See summary of soil descriptions	

UKAS	⊘ P\$
TESTING	PROFESSIONAL SOILS I
4043	A PHENN

Project Otter

Contract No:
PSL23/0045
Client Ref:
WIE17469

PSLRF025 Issue No.1 Approved by: L Pavey 03/01/202



LABORATORY REPORT



4043

Contract Number: PSL22/7580

Report Date: 20 December 2022

Client's Reference: WIE17469-WBH116

Client Name: Groundtech Consulting

First Floor Lloyd House Orford Court Greenfold Way WN7 3XJ

For the attention of: Michael Berry

Contract Title: Project Otter

Date Received: 28/11/2022 Date Commenced: 28/11/2022

A copy of the Laboratory Schedule of accredited tests as issued by UKAS is attached to this report. This certificate is issued in accordance with the accreditation requirements of the United Kingdom Accreditation Service. The results reported herein relate only to the material supplied to the laboratory. This certificate shall not be reproduced other than in full, without the prior written approval of the laboratory.

Checked and Approved Signatories:

A Watkins R Berriman S Royle (Director) (Quality Manager) (Laboratory Manager)

L Knight S Eyre M Fennell
(Assistant Laboratory Manager) (Senior Technician) (Senior Technician)

5 – 7 Hexthorpe Road, Hexthorpe,

Doncaster DN4 0AR tel: +44 (0)844 815 6641 fax: +44 (0)844 815 6642

e-mail: rberriman@prosoils.co.uk awatkins@prosoils.co.uk

Page 1 of

SUMMARY OF LABORATORY SOIL DESCRIPTIONS

Hole Number	Sample Number	Sample Type	Top Depth m	Base Depth m	Description of Sample
WBH116		В	0.20		Brown clayey silty SAND & GRAVEL.
WBH116		D	3.00		Brown mottled grey slightly gravelly sandy CLAY.
WBH116		U	9.00		Very stiff brown mottled grey CLAY.
WBH116		D	9.50		Brown mottled grey CLAY.
WBH116		U	18.00		Very stiff brown mottled grey CLAY.
WBH116		U	30.00		Very stiff brown mottled grey CLAY.
WBH116		В	30.50		Brown mottled grey CLAY.
WBH116		U	36.00		Very stiff brown CLAY.



Project Otter

Contract No:
PSL22/7580
Client Ref:
WIE17469


SUMMARY OF SOIL CLASSIFICATION TESTS

(BS1377: PART 2: 1990)


					Moisture	Linear	Particle	Liquid	Plastic	Plasticity	Passing	
Hole	Sample	Sample	Top	Base	Content	Shrinkage	Density	Limit	Limit	Index	.425mm	Remarks
Number	Number	Type	Depth	Depth	%	%	Mg/m^3	%	%	%	%	
			m	m	Clause 3.2	Clause 6.5	Clause 8.2	Clause 4.3/4	Clause 5.3	Clause 5.4		
WBH116		D	3.00		26			41	22	19	97	Intermediate Plasticity CI
WBH116		D	9.50		27			79	31	48	100	Very High Plasticity CV
WBH116		В	30.50		30			82	32	50	100	Very High Plasticity CV

SYMBOLS: NP: Non Plastic

^{*:} Liquid Limit and Plastic Limit Wet Sieved.



PLASTICITY CHART FOR CASAGRANDE CLASSIFICATION.






Contract No:
PSL22/7580
Client Ref:
WIE17469

BS1377 : Part 2 : 1990 Wet Sieve, Clause 9.2

Hole Number: WBH116 Top Depth (m): 0.20

Sample Number: Base Depth(m):

Sample Type: B



BS Test	Percentage
Sieve (mm)	Passing
125	100
75	100
63	100
37.5	100
20	92
10	81
6.3	74
3.35	68
2	63
1.18	58
0.6	51
0.3	39
0.212	32
0.15	28
0.063	23

Soil	Total
Fraction	Percentage
Cobbles Gravel Sand Silt/Clay	0 37 40 23

Remarks:

See Summary of Soil Descriptions





Contract No:
PSL22/7580
Client Ref:
WIE17469


BS1377: Part 2: 1990

Wet Sieve & Pipette Analysis, Clause 9.2 & 9.4

Hole Number: WBH116 Top Depth (m): 3.00

Sample Number: Base Depth(m):

Sample Type: D



BS Test	Percentage
Sieve (mm)	Passing
125	100
75	100
63	100
37.5	100
20	100
10	100
6.3	100
3.35	100
2	99
1.18	99
0.6	99
0.3	97
0.212	95
0.15	94
0.063	90

Particle	Percentage
Diameter	Passing
0.02	79
0.006	55
0.002	39

Soil	Total
Fraction	Percentage
Cobbles	0
Gravel	1
Sand	9
Silt	51
Clay	39

Remarks:

See Summary of Soil Descriptions





Contract No:
PSL22/7580
Client Ref:
WIE17469


BS1377: Part 2: 1990

Wet Sieve & Pipette Analysis, Clause 9.2 & 9.4

Hole Number: WBH116 Top Depth (m): 9.50

Sample Number: Base Depth(m):

Sample Type: D



BS Test	Percentage
Sieve (mm)	Passing
125	100
75	100
63	100
37.5	100
20	100
10	100
6.3	100
3.35	100
2	100
1.18	100
0.6	100
0.3	100
0.212	100
0.15	99
0.063	99

Particle	Percentage
Diameter	Passing
0.02	80
0.006	65
0.002	57

Soil	Total
Fraction	Percentage
Cobbles	0
Gravel	0
Sand	1
Silt	42
Clay	57

Remarks:

See Summary of Soil Descriptions





Contract No:
PSL22/7580
Client Ref:
WIE17469


BS1377: Part 2: 1990

Wet Sieve & Pipette Analysis, Clause 9.2 & 9.4

Hole Number: WBH116 Top Depth (m): 30.50

Sample Number: Base Depth(m):

Sample Type: B



BS Test	Percentage
Sieve (mm)	Passing
125	100
75	100
63	100
37.5	100
20	100
10	100
6.3	100
3.35	100
2	100
1.18	100
0.6	100
0.3	100
0.212	99
0.15	99
0.063	99

Particle	Percentage
Diameter	Passing
0.02	93
0.006	81
0.002	60

Soil	Total
Fraction	Percentage
Cobbles	0
Gravel	0
Sand	1
Silt	39
Clay	60

Remarks:

See Summary of Soil Descriptions





Contract No:
PSL22/7580
Client Ref:
WIE17469


WITHOUT MEASUREMENT OF PORE PRESSURE

BS1377: Part7: 1990: Clause 8

Hole Number: WBH116 Top Depth (m): 9.00

Sample Number: Base Depth (m):

Sample Type U



Diamete	er (mm):	103	Height	(mm):	207	Test:	UU Sing	gle Stage	Remarks:
Specimen	Moisture	Bulk	Dry	Cell	Corr. Max.	Shear	Failure	Mode	Undisturbed Sample
	Content	Density	Density	Pressure	Deviator	Strength	Strain	of	Sample taken from top of tube
	(%)	(Mg/m3)	(Mg/m3)	(kPa)	Stress	Cu	(%)	Failure	Rate of strain = 2 %/min
					(kPa)	(kPa)			Latex Membrane used 0.2 mm thick,
				3	(_{1 3}) _f	$^{1}/_{2}(_{1} _{3})_{f}$			Correction applied 0.36
1	26	1.98	1.57	180	465	232	5.0	Brittle	See summary of soil descriptions



	Contract No:
Duais at Otton	PSL22/7580
Project Otter	Client Ref:
	WIE17469